Model Stock code

# **EXTREME RANGE CAMERA**



BE-990C - Heavy duty heated camera

3042

1623

1559

1426

2871

1242

- Viewing angle (HxVxD) 95 x 72 x 125°
- IP69K
- Size (WxHxD) 83 x 60 x 66.5mm
- 3 year warranty



#### **Features**

- 6 Infrared LEDs for ultra-low light performance
- 10m illumination distance
- Heater
- Audio
- Mirror / Normal view
- 1/3" Sony CCD
- TV system: PAL
- TV lines: 420

### Power

- Power consumption: 3 Watts
- · Current: 0.25 Amps

#### **Durability & Standards**

- Mechanical vibration: 10G
- Mechanical shock: 100G
- Operating temperature: -30 to +80°C
- CE marked
- · EMC approved: e
- ISO 13766: 2006
- HALT tested

# **ELITE RANGE CAMERA**



Heated camera

**BE-800C** BE-800C(40) - Narrow viewing angle: 32 x 24 x 40° BE-800C(78) - Narrow viewing angle: 62.2 x 45 x 78° BE-890C - Waterproof to IP69K, No audio

- Viewing angle (HxVxD) 104 x 78 x 130°
- IP68
- Size (WxHxD) 88 x 71.5 x 79mm
- 3 year warranty



#### **Features**

- 5 Infrared LEDs for ultra-low light performance
- 5m illumination distance
- Heater
- Audio
- Day / Night sensor
- Mirror / Normal view
- 1/3" Sony CCD
- TV System: PAL
- TV lines: 380

#### **Power**

- Power consumption: 2.5 Watts
- Current: 0.25 Amps

## **Durability & Standards**

- Mechanical vibration: 20G
- Mechanical shock: 100G
- Operating temperature: -30 to +80°C
- CE marked
- EMC approved: e
- Approved for indirect vision (BE-800C only)
- ISO 13766: 2006
- HALT tested

# **ELITE RANGE CAMERA**

BE-810C - Heated shutter camera



Viewing angle (HxVxD)

- IP68
- Size (WxHxD) 123 x 85.4 x 80.4mm
- 3 year warranty

104 x 78 x 130°



## **Features**

- 6 Infrared LEDs for ultra-low light performance
- 5m illumination distance
- Shutter
- Heater
- Audio
- Day / Night sensor
- · Mirror / Normal view
- 1/3" Sony CCD
- TV System: PAL
- TV Lines: 380

### **Power**

- Power consumption: 4.5 Watts
- · Current: 0.35 Amps

## **Durability & Standards**

- · Mechanical vibration: 10G
- Mechanical shock: 100G
- Operating temperature: -20 to +70°C
- CE marked
- EMC approved: e
- Approved for indirect vision
- ISO 13766: 2006
- HALT tested