



金澤工業股份有限公司

Golden Loch Industrial Co., Ltd.

PRODUCT SPECIFICATION (產品規格)

PART NO. (圖號)	100-NF-SMAF-50	DATE (日期)	2019 / 12 / 30
TITLE (產品名稱)	N JACK TO SMA JACK BULKHEAD ADAPTOR		
MATERIAL AND FINISH (材質及表面處理)			
DESCRIPTION (名稱)		MATERIAL (材質)	FINISH (表面處理)
Center Contact (中心導體)		BERLLIUM COPPER	3 μ" Gold
Insulator (絕緣體)		PTFE	NATURAL
Outer Contact (外導體)		BRASS	NICKEL
Others (其它)	Gasket	SILICONE	RED
	Lock Washer	BRASS	NICKEL
	Hex Nut	BRASS	NICKEL
ELECTRICAL (電氣特性)			
Impedance (阻抗)		50 Ω	
Voltage Standing Wave Ratio (VSWR;駐波比)		1.3 Max. DC – 9 GHz	
Dielectric Withstanding Voltage (絕緣耐電壓)		1000 VRMS Min.	
Contact Resistance (導體阻抗)	Center Contact (中心導體)	6 mΩ Max.	
	Outer Contact (外導體)	2 mΩ Max.	
Insulation Resistance(絕緣阻抗)		5000 MΩ Min.	
MECHANICAL (機械特性)			
Insulator Retention (絕緣體承受力) : 6 lbs. Min.			
Contact Retention (中心導體承受力) : 6 lbs. Min.			
REMARKS (備註)			

APPROVED:

REVIEWED:

DRAFTED: