



RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS
 2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 4. TEFLON
 5. PHOSPHOR BRONZE

1. CRIMPED FERRULE
HEX CRIMP SIZE .429"
2. CONTACT PIN TO SOLDER

9	FERRULE	NOTE 1	NOTE 2	1	FR-112-124-158	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	PART NO.		<h1 style="margin: 0;">G.L.I.</h1>	
8	CONTACT PIN	NOTE 1	NOTE 3	1	5824-1000-8-2.4		APPROVED	DATE		TITLE
7	RETAINER RING	NOTE 5	NATURAL	1	5824-1000-7			02-11-'11		N CRIMP PLUG (FOR RG-214/U CABLE)
6	GASKET	SILICONE	RED	1	GS-80-156-15		CHECKED	DATE		DRAWING NO.
5	CONTACT BODY	NOTE 1	NOTE 2	1	5824-1000-5			02-11-'11		5824-1121A1-18-50
4	INSULATOR	NOTE 4	NATURAL	1	5824-1000-4A		DRAWN	DATE		FILE NO.
3	BARREL	NOTE 1	NOTE 2	1	5824-1000-3-17			02-11-'11		R:\D\G\DWG\5824\1121A1\18\50
2	BODY	NOTE 1	NOTE 2	1	5824-1000-2					
1	SHELL	NOTE 1	NOTE 2	1	5824-1000-1					
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2.5/1	ISSUE	A	