



📄(0)



📄(0)



- ABOUT**
- NEWS**
- PRODUCTS**
- CONTACT**



BNC Connector

Click 📄 to select products and contact the supplier.

Jack (Female) > Crimp Type (50 Ohm) > BNC Connector

BNC Connector Crimp Jack for RG58 LMR195



NO. 900-6121B1-06-50D

Quantity

Add to Inquiry

Product Detail

Specifications

BNC Connector Crimp Jack for RG58 LMR195

Material and Plating

Body/Brass/Nickel

Insulator/Delrin

Center Contact/Phosphor Bronze/3u" Gold

Electrical(50 Ω)

Impedance: 50 Ohm

Frequency Range: DC ~ 4 GHz

VSWR: 1.35 max.

Insertion Loss: ≤ 0.3 dB

Insulator Resistance: $\geq 5 \text{ G}\Omega$
Center Contact Resistance: $\leq 1.5 \text{ m}\Omega$
Outer Contact Resistance: $\leq 1 \text{ m}\Omega$
Test Voltage: 1,500 V rms
Working Voltage: 400 V rms
Power Handling: $\leq 80 \text{ W @ 2 GHz}$

Electrical(75 Ω)
Impedance: 75 Ohm
Frequency Range: DC ~ 12 GHz
VSWR: 1.35 max.
Insertion Loss: $\leq 0.5 \text{ dB}$
Insulator Resistance: $\geq 5 \text{ G}\Omega$
Center Contact Resistance: $\leq 1.5 \text{ m}\Omega$
Outer Contact Resistance: $\leq 1 \text{ m}\Omega$
Test Voltage: 1,500 V rms
Working Voltage: 400 V rms
Power Handling: $\leq 80 \text{ W @ 2 GHz}$

Environmental
RoHS and REACH compliant

Certificate
ISO 9001 TS 16949

Ethical Sourcing
Conflict Minerals Reporting Template (CMRT)



[ABOUT](#) | [NEWS](#) | [PRODUCTS](#) | [CONTACT](#)

© Copyright Golden Loch Ind. Co., Ltd. All rights reserved. Design by DAKE.